


PROFILÉS À FROID

Panne C



PROFILS	Dimensions				A (cm ²)	P (Kg/m)	Relation Y-Y I _y (cm ⁴)	Relation Y-Y W _y (cm ³)	Relation Z-Z I _z (cm ⁴)	Relation Z-Z W _z (cm ³)	
	h (mm)	b (mm)	c (mm)	t (mm)							
C200	C200x3.0	200	80	25	3.00	11.45	9.09	704.1	71.48	99.16	18.56
	C200x2.5	200	80	25	2.50	9.6	7.64	595	60.25	84.9	15.78
	C200x2.0	200	80	25	2.00	7.71	6.16	481.4	48.63	69.16	12.84
	C200x1.5	200	80	25	1.50	5.78	4.66	363.2	36.59	52.65	9.73
C170	C170x3.0	170	60	15	3.00	8.79	6.97	374.3	44.82	37.22	8.87
	C170x2.5	170	60	15	2.50	7.39	5.87	317.9	37.96	32.16	7.63
	C170x2.0	170	60	15	2.00	5.95	4.75	258.5	30.77	26.57	6.27
	C170x1.5	170	60	15	1.50	4.47	3.60	195.7	23.23	20.41	4.79
C150	C150x2.5	150	50	12	2.50	6.26	4.97	204.5	27.73	17.8	5.01
	C150x2.0	150	50	12	2.00	5.05	4.02	166.9	22.55	14.83	4.15
	C150x1.5	150	50	12	1.50	3.79	3.05	126.7	17.07	11.48	3.19
C100	C100x2.5	100	50	12	2.50	5.04	3.99	78.8	16.16	15.6	4.79
	C100x2.0	100	50	12	2.00	4.07	3.24	64.6	13.19	13	3.96
	C100x1.5	100	50	12	1.50	3.06	2.46	49.3	10.01	10.07	3.05
C80	C80x2.5	80	40	12	2.50	4.04	3.20	39.5	10.2	8.2	3.26
	C80x2.0	80	40	12	2.00	3.28	2.61	32.6	8.37	6.9	2.72
	C80x1.5	80	40	12	1.50	2.48	1.99	25.1	6.38	5.38	2.1