


PROFILÉS À FROID

Panne Z



PROFILS	Dimensions					A	P	Relation Y-Y			Relation Z-Z	
	h (mm)	b1 (mm)	b2 (mm)	c (mm)	t (mm)			I _y (cm ⁴)	W _y (cm ³)	I _z (cm ⁴)	W _z (cm ³)	
Z300	Z300x3.0	300	78	69	22	3.00	14.48	11.37	1930.51	117.96	76.81	12.47
	Z300x2.5	300	78	68	22	2.50	12.07	9.48	1613.81	98.5	64.03	10.36
	Z300x2.0	300	77	67	22	2.00	9.65	7.85	1289.83	78.83	50.45	8.21
Z250	Z250x3.0	250	78	69	22	3.00	12.98	10.19	1284.82	90.95	70.86	11.99
	Z250x2.5	250	78	68	22	2.50	10.82	8.50	1074.49	76	59.09	9.96
	Z250x2.0	250	77	67	22	2.00	8.65	6.79	858.66	60.85	46.59	7.9
Z200	Z200x3.0	200	72	62	21	3.00	11.03	8.66	738.06	62.97	51.44	9.72
	Z200x2.5	200	72	61	21	2.50	9.2	7.22	617.62	52.67	42.93	8.07
	Z200x2.0	200	71	60	21	2.00	7.35	5.77	493.38	42.19	33.83	6.4
Z180	Z180x2.5	180	66	60	21	2.50	8.52	6.69	476.22	44.7	36.25	7.45
	Z180x2.0	180	65	59	21	2.00	6.81	5.35	380	35.82	28.56	5.91
	Z180x1.5	180	65	59	21	1.50	5.12	4.02	287.53	27.1	21.56	4.47

